

Low-Temp Dishwasher Conserver | 低溫多功能洗碗機



(Shown C1 L/Temp)

Model	Racks/hr	Amp/Volts/Phase	Each(\$)
AJ-44CS	248	48/208V/3PH	9,450

FEATURES/BENEFITS

- Dishwasher, Door Type, low temperature chemical sanitizing, universal (straight-thru/corner) type, approximately 35 racks/hour capacity, all stainless steel finish, 3-way precision dispenser
- Automatic 90 seconds timed wash, flush and rinse cycle.
- Built-in dispensing pumps(3) for detergent, rinse agent, and sanitizer are controlled by cycle timer and each has individual priming switch.
- Cycle start switches are located on both sides of control box for ease of operation regardless of direction of dishwasher flow. Safety door switch.
- Convertible from straight-through to corner and vice versa without additional parts.

Low-Temp Conserver 24 Series 低溫多功能洗碗機



(Shown C24LT)

FEATURES/BENEFITS

- Dishwasher, Undercounter, low temperature, chemical sanitizing, approx 30 racks per hour capacity, 2 minutes cycle, only 1.2 gal of water per cycle, without side panels and top.
- All stainless steel finish.
- Requires 140° F incoming water supply. Automatic fill.
- Recirculating wash and rinse.
- Simplified controls for easy service and operation.
- Manual switch for extended wash and delimiting.

Hi-Temp Single-Tank Rack Conveyor Dishwashers 高溫自動傳送式洗碗機



(Shown AJ-44CE)

Model	Racks/hr	Amp/Volts/Phase	Each (\$)
AJ-44CE	248	49/208/3; 83/208/1	9,142
AJ-44CE	248	76/230/1; 45/230/3	9,142
AJ-44CE	248	29/380/3; 22/460/3	9,142
AJ-44CS	248	7/208/3; 10/208/1	9,814
AJ-44CS	248	11/230/1; 7/230/3	9,814
AJ-44CS	248	4/380/3; 4/460/3	9,814

Note:

AJ-44CE : Electric Tank Heat need immersion-type heating elements with low water protection, sold separately \$ 940.

AJ-44CS: Steam coil mounted in wash tank, requires 10-20 PSI steam supply, sold separately \$ 1620.

Booster Heater Info (optional):

-Built-in 36 KW Hatco booster heater, 40 ° F Rise sold separately \$ 2130.

-External 45KW Hatco booster heater, 70 ° F Rise sold separately \$ 2430.

-Steam Booster Heater: must be installed with a steam pressure regulator if steam supply exceeds 20 PSI, sold separately \$ 2020.

FEATURES/BENEFITS

- Dishwasher, Conveyor Type, high temperature sanitizing, single tank design, approx. 248 racks/hour capacity.
- 0.94 gallons per rack Hi-temp sanitizing rinse.
- Standard 25" clearance allows owner operators the ability to wash large utensils, trays, and bun pans.
- Complete Right-to Left and Left-to-Right convertibility in the field.
- Totally electromechanical; no solid controls utilized. Fully automatic including auto-fill. Completely self-draining stainless steel wash pump.
- A long 18" wash section as well as 18" separation between wash and rinse produces superior results.