

Options & Accessories-Restaurant Ranges

Description	Model	W x D x H	Each(\$)
Pasta Cooker	PC-1	21" x 18" x 10"	780
Chrome plated oven rack (in lieu of standard rack)			20
Stainless steel rear (includes riser's rear)			
36" wide standard oven range			300
36" wide convection oven range			380
60" wide standard oven range			360
60" wide convection oven range			460
Extra cold roll rack for standard oven		26" x 25"	30
Extra plated rack for standard oven		26" x 25"	50
Extra plated rack for convection oven		26" x 25"	50
Casters (in lieu of legs)			
Locking (2 each) and standard (2 each)		5" diameter	170
Casters (ordered separately)			
Locking (2 each) and standard (2 each)		5" diameter	230
Export packaging			
Units up to 36" wide			30
Units over 36" wide			40
Auxiliary griddle plate	4450000	12" x 24" x 1"	200
3/16" plate, with handles			
Hot Tops * Not available on any griddle combination			
Factory Installation Only	C-046	12" x 24"	490
Each top replaces two burners, front-to-back			

Limited Warranty

Southbend warrants that the equipment, as supplied by the factory to the original purchases, is free from defects in materials and workmanship. Should any part thereof become defective as a result of normal use within the period and limits defined below, then at the option of Southbend such parts will be repaired or replaced by Southbend or Authorized Service Agency. This warranty is subject to the following conditions:

Repairs under this warranty are to be performed by a Southbend Authorized Service Agency. Southbend cannot be responsible for charges incurred or service performed by non-Southbend Authorized Agencies. In all cases the closest Southbend Authorized Service Agency must be used.

Time Period:

One year labor, one year parts effective from the date of original purchase. The authorized service agency may at his option require proof of purchase.

Exceptions to standard warranty, effective within above limitations:

- Glass Window, Door Seals, Rubber Seals, Light Bulbs, Ceramic Bricks,
  - Sight Glasses, Cathodic Descalers or Anodes, Broiler, Briquettes and Drip Shields...90 days material and labor
  - Stainless Steel Fry Pot.....4 years extended material warranty on fry pot -- no labor
  - Stainless Steel Open Top Burners.....4 years extended material warranty on burners only -- no labor
  - Pressure Steam Broiler Shell.....Prorated 4 years extended warranty on boiler shell only -- no labor.
- Boiler Shells which have not been properly maintained will not be covered by warranty.

In all cases, parts covered by a five year warranty will be shipped FOB the factory after the first year.

Exclusions:

- Equipment failure relating to improper installation. Examples are: improper utility connection, improper utilities supply and problems due to ventilation.
- Equipment that has not been properly maintained. Examples are: calibration of controls, adjustments to pilots and burners, damage from improper cleaning, and water damage to controls.
- Equipment that has not been used in an appropriate manner, or has been subject to misuse or misapplication, neglect, abuse, accident, damage during transit or delivery, fire, flood, riot, or act of God.

If the equipment has been changed, altered, modified or repaired by other than a qualified service technician during or after the one year limited warranty period, then the manufacturer shall not be liable for any damages to any person or to any property which may result from the use of the equipment thereafter.

Equipment failure caused by inadequate water quality is not covered under warranty. WATER QUALITY must not exceed the following limits: Total Dissolved Solids (TDS) - 60 PPM (Parts Per Million). Hardness - 2 Grains or 35 PPM, PH Factor - 7.0 to 7.5. Water pressure 30 PSI minimum, 60 PSI maximum. Boiler maintenance is the responsibility of the owner and is not covered by warranty.

This warranty does not cover service performed at overtime or premium labor rates nor does Southbend assume any liability for extended delays in replacing or repairing any items in the equipment beyond the control of Southbend. "Southbend shall not be liable for consequential or special damages of any nature that may arise in connection with such product or parts." Should service be required at times which normally involve overtime or premium labor rates, the owner shall be charged for the difference between normal service rates and such premium rates.

This warranty only covers product shipped into the 48 contiguous United States and Hawaii. There will be no labor coverage for equipment located on any island not connected by roadway to the mainland.

This equipment is intended for commercial use only. Warranty is void if equipment is installed in other than commercial application.

Warranty on all replacement parts which are replaced in the field by Southbend Authorized Agencies will be limited to three months on labor, six months on materials (parts) effective from the date of installation. See LIMITED WARRANTY - REPLACEMENT PARTS for conditions and limitations.

"THE FOREGOING WARRANTY IS IN LIEU OF ANY AND ALL OTHER WARRANTIES EXPRESSED OR IMPLIED INCLUDING ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS, AND CONSTITUTES THE ENTIRE LIABILITY OF SOUTHBEND, IN NO EVENT DOES THE LIMITED WARRANTY EXTEND BEYOND THE DURATION OF ONE YEAR FROM THE EFFECTIVE DATE OF SAID WARRANTY."

版權所有，不得翻印。價格隨時變化，無需通知。如印刷有誤，恕不負責。

Copyright 1999-Win Restaurant Supplies, Inc. All rights reserved.  
 All prices subject to change without notice. There is no responsibility for printing errors.

Rapid Steamers-Stacked and Quad Systems

Description	Model	W x D x H	Each(\$)
Two R2 steamers mounted on stainless steel stand	R2-SS	20" x 30" x 69"	4,950
Four R2 steamers mounted on stainless steel stand	R2-QS	36" x 28" x 66"	9,330
Stand only (holds two R2 steamers)	SS-20	20" x 28" x 48"	600
SS-20 with shelf		N/A	710
Stand only (holds four R2 steamers)	Q-36	36" x 28" x 48"	710
<b>OPTIONS</b>			
Single stand	ST-16	16" x 35" x 34"	260
Tandem stand	ST-32	32" x 35" x 34"	420
220V, 50/60Hz			120
220VAC, 50 Hz, 3-Phase			120
240VAC, 50 Hz, 3-Phase			120
480VAC, 60 Hz, 3-Phase			120
Stacking kit for field mounting	1176777		110
Tandem kit for side-by side mounting			30
4" SS Legs (set of 4, R2 steamers)			50